




- △ Adjustable beam angle COB LED track light series.
- △ High purity lathe aluminum housing with fine paint finishing.
- △ Excellent ventilation to dissipate heat that ensures stable working.
- △ Professional optical lens with 15 to 60 degree adjustable beam angle.
- △ Smoothing and comfortable appearance, 2,3 and 4 steps optional.
- △ Bridgelux chips COB inside, high Ra>80/90, high lumen 150Lm/W.
- △ COB LED meets standards LM80 / EN62471 / RoHS / REACH144.
- △ High quality Isolated constant current driver, no flicker, high PF>0.90.
- △ LED driver meets standards CE / CB / TUV / BIS / CCC / SAA / FCC.
- △ Reliable quality and stable performance, low heat and low light decay.
- △ 50,000 hours life time, eco-friendly materials, up to 80% power saving.

(30W luminous intensity and lux distribution diagrams)





Model	Size	Step	Power	Beam Angle	PF	Ra	Flicker	Voltage	Lumen
CL-TL004012	65x140x160mm	2*3*4	12W	15°-36°	>0.90	>80/90	No	90-350VAC	1100LM
CL-TL004024	90x210x180mm	2*3*4	24W	15°-36°	>0.90	>80/90	No	90-350VAC	2200LM
CL-TL004030	95x185x220mm	2*3*4	30W	15°-36°	>0.90	>80/90	No	90-350VAC	2700LM



- △ Full aluminum with big lens COB LED tracking light series.
- △ High purity lathe aluminum housing with fine paint finishing.
- △ Excellent ventilation to dissipate heat that ensures stable working.
- △ Professional optical big lens gives outstanding focusing beam.
- △ United body heatsink, aluminum driver box, 2,3 and 4 steps optional.
- △ Bridgelux chips COB inside, high Ra>80/90, high lumen 150Lm/W.
- △ COB LED meets standards LM80 / EN62471 / RoHS / REACH144.
- △ High quality Isolated constant current driver, no flicker, high PF>0.90.
- △ LED driver meets standards CE / CB / TUV / BIS / CCC / SAA / FCC.
- △ Reliable quality and stable performance, low heat and low light decay.
- △ 50,000 hours life time, eco-friendly materials, up to 80% power saving.

(30W luminous intensity and lux distribution diagrams)



Model	Size	Step	Power	Beam Angle	PF	Ra	Flicker	Voltage	Lumen
CL-TL005030	85x210x150mm	2*3*4	30W	24°/36°/60°	>0.90	>80/90	No	90-350VAC	2700LM